

INTRODUCING DEMCO'S NEWEST GRAIN CART



1000 & 1100 SINGLE AUGER GRAIN CARTS

Designed with the operator in mind, Demco's new 1,000 & 1,100 bushel corner auger grain carts allow the operator optimal visibility while unloading grain. New features on these models include a 20" balanced auger with 3/8" Ultraflyte auger flighting, and an optional 5 point scale system. Demco grain carts are tough and reliable allowing the operator maximum uptime for an efficient harvest.

BUSHEL CAPACITY

	1000	1100
Level Full	1000	1100

Bushel capacity measured with #2 corn at 15% moisture content (56 lb. test weight)

STANDARD FEATURES

- 1 $\frac{3}{4}$ - 1000 RPM PTO
- **Protect auger driver and tractor PTO** with the automatic reset "cut-out" clutch with overrunning clutch
- Adjustable austempered cast hitch, fits category 4 or 5 hammer strap tractor drawbar
- **High visibility** - reflective decals
- LED Tail, flasher/turn signal lights and auger spotlight for nighttime operation
- **Tube and truss design** - adjustable axle
- Welded box construction with silicone sealed seams resists rust and corrosion
- Heavy duty spindles and hubs

AUGER

- 20" diameter balanced auger with 3/8" flighting and Posi-Drive connection
- UltraFlyte made with 1008/1010 high carbon steel including a thicker outer edge, resulting in up to 50% longer wear and faster conveying
- Forward reach auger for optimum operator visibility
- 2 stage unload auger folding cylinder

OPTIONS

- Roll top tarp
- Ergonomic pendant control
- Scale kits
- Hydraulic Drive Kit - High Speed /Torque



1000 & 1100

SINGLE AUGER GRAIN CARTS



MODEL - Wheels

** All grain carts require a Demco axle*

1000 Grain Cart - Gray	9445175
1000 Grain Cart - Red	9445172
1000 Grain Cart - Green	9445173

1100 Grain Cart - Gray	9445179
1100 Grain Cart - Red	9445176
1100 Grain Cart - Green	9445177

AXLE TYPE

Axle with 1050/50 R32 195 Load Index tires (Silver)	9445468
Axle with 900/60R32 - 185 Load Index Lug Tire	9445467
Track system 36" wide	9445466

FACTORY INSTALLED ACCESSORIES

1000/1100 Roll Up Tarp* (end caps reduce load capacity)	9440152
Scale 5 Point (Less console)	9440154
12" Auger Spout Extension	9440122
Cat 4 Bull-Pull Hitch™ (I.L.O. Cast Hitch)	9440125
Cat 5 Bull-Pull Hitch™ (I.L.O. Cast Hitch)	9440127
High Speed High Torque Hydraulic Drive (70 GPM Max oil flow and 3 remote outlets required) in lieu of PTO Drive	9445619
Pendant Grip Control	9440081

FIELD INSTALLED ACCESSORIES

1000/1100 Roll Up Tarp* (end caps reduce load capacity)	9440151
Scale 5 Point (Less console)	9440153
Cat 4 Bull-Pull Hitch™	9440126
Cat 5 Bull-Pull Hitch™	9440128
12" Auger Spout Extension	9440121
Pendant Grip Control	9440104
High Speed High Torque Hydraulic Drive (70 GPM Max oil flow and 3 remote outlets required)	9445618

ACCESSORIES

640 Console with harnesses	9440111
2060 Console with harnesses	9440116
ISO Bus ECU with harnesses	9440131
Wireless Scale Libra Cart*	9440112
Wireless Scale Libra Cart (Requires optional pendant grip control) w/ Auto Gate Shutoff*	9440149
12 VDC Printer with interface cable	14990
Slip plate coating	SLIPPL
12' Harness Extension for Pendant	17060

** Roll tarps: some dealer assembly required. Tarp & bows are removed due to shipping restrictions*



BACK LIT PENDANT GRIP

Optional ergonomic pendant operates grain flow gate, auger fold, and adjustable spout

Standard Feature



HYDRAULICS NOTES:

- A standard grain cart requires three hydraulic remotes.
- Optional Pendant Control manages slide gate, folding auger and adjustable spout. Requires one hydraulic remote.
- 70 GPM max oil flow is required for high speed high torque hydraulic unloading drive.

COLORS AVAILABLE:



NOTE: Demco grain carts are not to be towed down the road loaded