DEMCO

Lawn & Garden Pro Series Sprayers

Doing Our Best to Provide You the Best

www.demco-products.com • 1.800.543.3626

DEMCO

BETTER AGITATION, BETTER DRAINAGE

Many lawn sprayer manufacturers are good at supplying an affordable, easy to assemble product. But its functionality is a big secret until you use it for the first time. Less than desirable agitation and poor drainage are the results acquired from off-the-shelf tank designs.

At Demco we designed a tank specifically for our Pro Series sprayers. A molded-in baffle system provides excellent circulation and chemical suspension. And a large deep sump insures uninterrupted application.

14 & 25 GALLON SPRAYERS

Features

- 5″ fillwell, 1″ sump, 1⁄2″ outlet with agitation
- 15″ spray gun with adjustable nozzle for 14 gal sprayer
- 18″ handgun with adjustable nozzle for 25 gal sprayer
- 14 gal has 1.8 GPM electric pump. 3 GPM pump optional
- 25 gal has 5 GPM electric pump
- Pressure gauge and regulating valve standard
- 80″ or 144″ Booms available for 14 gallon sprayer
- 12′, 18′, 21′ or 30′ Booms available for 25 gallon sprayer

110 & 150 GALLON SPRAYERS

Features

- 110 or 150 gallon polyethylene tank features sump, molded sight gauge and large fillwell
- Heavy duty formed steel skid frame (W-30″ x L-70″)
- 5 GPM electric pump, 4 roller pump or gas engine with centrifigal pump-3.5 HP B & S or 4 or 5.5 HP Honda
- 18″ handgun with 15′ hose
- 12′, 18′ or 21′ booms

Optional lawn and turf handgun

40, 60, & 80 GALLON SPRAYERS

Features

- 40, 60 & 80 gal tank sizes available
- Trailer, skid & rear mount models
- 40 gal boom options of 80", 12' or 18'
- 40, 60, & 80 gal tank sizes. 40 gal comes with 5 GPM electric pump
- 60 & 80 gal boom options of 80", 12', 18', 21 'or 30'
- 40, 60, & 80 gal tank sizes. 60 & 80 gal pump options of electric 5 GPM, 3.5 HP B&S engine with C4101 GE pump, 4 HP Honda with "Silver Cast" pump, 3 HP Honda with Ace centrifugal pump or PTO 6 Roller pump
- Sloped bottom sump for total drainage
- Molded-in baffling for agitation
- 5" fillwell and 1 1/4" outlet
- Gallon and liter markings on the tank
- Rugged 12 gauge formed steel skid frame
- 15 x 6 flotation tires for 40 gallon trailer
- 18 x 9.50 flotation tires for 60 & 80 gallon trailer models
- Handgun with 15' hose
- 2 nozzle boomless kits available
- Electric skid models have control arm as standard equipment

9464077
80B25

9464105
DB12

9464090
DB21TDF

150 & 200 GALLON SPRAYERS

Features

- 2" ball coupler hitch
- Single or tandem axles
- Walking tandems feature "lock out" for rigid axle spraying
- 21', 30' and 40' booms
- PTO 6 roller pump, 6.5 HP Power Pro TM or 5.5 HP Honda gas engines with centrifugal pump
- 150 or 200 gallon polyethylene tank with jet agitation, sump molded sight gauge and fillwell
- Trailer frame features height adjustment of up to 18" ground clearance and adjustable wheel spacing of 44" to 90" maximum centers
- Single axle has 24x12 turf tires
- Walking tandems have 22x11x8 pneumatic tires
- 2 1/2 gallon clean water tank

3 POINT SPRAYERS

RMLE SERIES SPRAYERS - 300, 400, & 500 GALLON

The Demco RMLE Series sprayers are 3 point mounted sprayers available in capacities of 300, 400, or 500 gallons. The RMLE Series sprayers are an excellent choice to be your primary sprayer or a secondary sprayer to go with your self-propelled unit.

- 300, 400 or 500 gallon tank with jet agitation, molded sight gauge, sump and fillwell with no-splash cover.
- Rear mount brackets are complete with saddles, tank straps and all necessary bolts.
- Category "2" or "3" rear mount brackets may be used with "Quick Attach" three point hookup.
- Large, convenient platform with safety rail and ladder for easy filling of the tank.
- Retractable, built-in ground stand for storage when empty.
- A clean water tank is conveniently mounted on the rear mount unit.
- Available with three section electric controls for boom spraying.

RM SERIES SPRAYERS - 150 & 200 GALLON

The Demco RM Series sprayers are 3 point mounted sprayers available in capacities of 150 or 200 gallons. Many different boom and pump options are available so that you can have this sprayer equipped to best meet your needs. This high quality sprayer is perfect for spot spraying or spraying smaller fields and pastures.

- 150 or 200 gallon tank with jet agitation, molded sight gauge, sump, fillwell with no-splash cover.
- Rear mount brackets are complete with saddles, tank bands and all necessary bolts.
- Rear mount brackets will fit categories "1" and "2".
- Unit may be used with a "Quick Attach" three point hookup.
- Non-retractable built-in ground stand for storage when empty.
- Hypro® 8 roller PTO pump (C7560D) will deliver 22 GPM at 1000 RPM, 12 GPM at 540 RPM and 300 PSI max.
- 21', 30' and 40' Truss-T booms feature vertical and horizontal boom breakaway, no drip diaphram check nozzles spaced at 20".
- Handgun with 25' of hose (optional)

RM SERIES SPRAYERS - 600 GALLON

The new Demco 600 gallon rear mounted sprayer is just the type of unique product you can expect from Demco to help meet the needs of your farming operation. The design and placement of the tank allows this high capacity 3-point sprayer to mount closer to the tractor. The tank has a sump for superior product clean-out and drainage.

- 600 gallon tank with 16 inch fillwell, jet agitation, molded sight gauge, and large centered drainage sump.
- Category "3" or "4" rear mount brackets may be used with "Quick Attach" three point hookup.
- Large, convenient platform with safety rail and ladder for easy filling of the tank.
- Retractable, built-in ground stand for storage when empty.
- A clean water tank is conveniently mounted on the rear mount unit.
- Available with 45, 60, 66 or 80/90' front fold booms

DEMCO

Doing Our Best to Provide You the Best

4010 320th Street • Boyden, Iowa 51234
1.800.543.3626
www.demco-products.com

AS11009 Rev 13 10/18