



Unbeatable Hauling Power, On the Road or Off www.demco-products.com • 1.800.543.3626



TWIN RAMPS

KINGPIN

SETTING 24"

Standard on beaver tail trailers



HOLLAND ATLAS 55 LANDING GEAR 55,000 lb capacity



RAMP DESIGNED TO CARRY EXTRA CARGO Groove fits 2x4 board



1 1/8" APITONG FLOORING solid board with mitered joints, NO but joints



THE CORROSION SOLUTION

CORSOL® corrosion solutions are the result of PRP® Industries' METAL POLYMERIZATION® process. The result is a field-proven corrosion solution that prevents the devastating effects of undercutting and blistering on Demco's steel products.





FIELD-PROVEN TESTING Washington State Department of Transportation is particularly hard on its snow removal equipment. Exposure to months of harsh conditions and corrosive road salt while operating in mountainous regions is why we chose their equipment to field test CORSOL® corrosion solutions. The two salt spreader trucks shown below were brand new in 2008 and have since operated continuously out of the same facility.



DOUBLE HINGE RAMP with built in stabilizer



4 SPRINGS PER RAMP 2 springs assist in raising and 2 springs assist in lowering



Scan this QR Code to see how easy the ramps are to move up and down





WINCH TRACK

Track is standard on the driver's side (optional on passenger's side), sliding winches optional

ABS Standard on 1 axle Optional on second axle

ANTI-SAIL MUDFLAPS Rigid, heavy duty mudflaps



OPTIONS



UPPER RAMPS Removable



FRONT BULKHEAD Removable



STEEL FLOORING 48' & 53' no beavertail



DISC BRAKES



TOOLBOX Located between wheels or up front



ALUMINUM RIMS Steel rims are standard

BEAVER TAIL WITH 3 RAMPS

OTHER TRAILER OPTIONS

- Holland SAF Air Ride Suspension
- Manual Dump Valve
- Electric Dump Valve
- Scale for Manual or Electric Dump Valve

TIRE PACKAGE OPTIONS

- 255/70R22.5 Import Radial LRH
- 255/70R22.5 Domestic Radial LRH Dunnlap SP160



3 AXLE CONFIGURATIONS: TANDEM, SPLIT TANDEM, TRIPLE

Air ride suspension is standard on triple axle trailers

STEEL DROP DECK TRAILER MODELS

		Suspension			
Model	Trailer Description	Closed	10:1 Spread	Triple Axle	Tare Weight
DD40	40' Tandem Axle	~	n/a	n/a	10,720 lbs
DD45	45' Tandem Axle	V	V	n/a	11,420 lbs
DD48	48' Tandem Axle	V	✓	n/a	11,980 lbs
DD53	53' Tandem Axle	V	V	n/a	12,860 lbs
DD40-5	40' Tandem Axle + 5' Beaver Tail with Twin Ramps	V	n/a	n/a	11,980 lbs
DD43-5	43' Tandem Axle + 5' Beaver Tail with Twin Ramps	V	V	n/a	12,420 lbs
DD45-5	45' Tandem Axle + 5' Beaver Tail with Twin Ramps	V	✓	n/a	12,640 lbs
DD48-5	48' Tandem Axle + 5' Beaver Tail with Twin Ramps	V	V	n/a	12,880 lbs
DD48-3	48' Triple Axle	n/a	n/a	V	12,840 lbs
DD53-3	53' Triple Axle	n/a	n/a	V	13,720 lbs
DD48-5-3	48' Triple Axle + 5' Beaver Tail with Twin Ramps	n/a	n/a	V	15,130 lbs

^{*} Upper ramps add 250 lbs.

STANDARD DESIGN AND PERFORMANCE CHARACTERISTICS

- Main Beams Designed with Camber
- Web 1/4" Grade 100 High Yield Steel
- Flange 3/8" x 5" Grade 100 High Yield Steel
- Cross Members 4" x 3.2# 80,000 Yield Jr. I-Beam on 16" Centers
- Side Rails 6" x 8.2# Structural C Channel
- Stake Pockets & Pipe Spooling at 9" Intervals
- Rub Rail 2" x 3/8" Flat Steel

- Upper Deck Length of 11 Feet
- Transition drop of 19.5" from Upper Deck to Lower Deck
- 102" Overall Trailer Width
- 40 3/4" Lower Deck Height
- Beam Rating Lower Deck 50K lbs Per 10 Linear Feet
- 68K Gross Vehicle Weight Rating on closed Tandem & Spread Axle Trailers
- 77.5 Gross Vehicle Weight Rating on Triple Axle Trailers

The information contained herein is general in nature and is not intended for specific application purposes. Demco Manufacturing reserves the right to make changes in specifications or products at any time without notice or obligation. Trailers pictured in this brochure may feature optional equipment.



Doing Our Best to Provide You the Best

4010 320th Street • Boyden, Iowa 51234 1.800.543.3626

www.demco-products.com