




Doing Our Best to Provide You the Best

TB20043, Rev 1
10/16

SENTRY ADAPTOR KIT 9523061 for Blue Ox



Not for use with Blue Ox Ascent

OPERATOR MANUAL

ITEM	PART #	QTY	DESCRIPTION
1	13728-81	2	SENTRY MOUNTING CLEVIS f/ BLUE OX
2	07164-95	2	BOLT, .50 X 3
3	02178	2	NUT, .50 NYLON LOCK
4	03809	4	WASHER, WEAR BUSHING (THICK)
-	07399	4	WASHER, WEAR BUSHING (THIN)
5	07908-95	4	HEAVY WASHER
6	10704-95	2	BUSHING 1" OD X .875 LONG
7	00059	4	WASHER, .375 FLAT
8	02592	2	NUT, .375 NYLON LOCK
Please order replacement parts by PART NO. and DESCRIPTION			

ITEM	PART #	QTY	DESCRIPTION
9	13666	4	CLEVIS SPACER f/ EXCALIBAR II
10	13667	4	CLEVIS SPACER f/ COMMANDER
11	13668	4	BUSHING f/ .375 COMMANDER BOLT
12	13669-95	2	CLEVIS BOLT f/ COMMANDER
13	13496-95	2	ATTACHING PIN
14	02397	2	LYNCH PIN
15	00698-95	2	BUSHING 1" LONG
Please order replacement parts by PART NO. and DESCRIPTION			



CAUTION

Safety is of utmost importance at all times. There are several items that must be checked each time before using and while using a tow bar.

Before allowing anyone to hook up or operate a tow bar, be sure they have read and understand the proper operating procedure.

DO NOT use worn or damaged cables and/or pins.

Be sure the **SAFETY CABLES** are hooked, chassis to chassis, to both the towing and towed vehicles using the crisscross method.

Check clearance between vehicles in a turning situation.

Check base plate mounting bolts for tightness and frame for metal fatigue.

Do not load the towed vehicle with anything as you may exceed the towing capacity of the tow bar.

Keep fingers away from pivot points to prevent personal injury.

Be sure the steering components of the towed vehicle are properly aligned.

NOTE: This unit can be backed up in moderate increments. Any severe backwards cornering could result in damage to the Tow Bar and/or towed vehicle chassis.

For automatic transmissions: Consult your vehicle owners manual for towing suitability with the drive shaft connected. Otherwise, the towed vehicle will have to be equipped with a transmission pump or drive shaft disconnect.

Check to make sure that all lights are in proper working order.

The information on towability of vehicles is reprinted with permission of MotorHome® Magazine, and is believed to be reliable. However, **Demco does not** warrant the information to be correct. Always consult your towed vehicle owner's manual and follow towing instructions. Each year, **MotorHome® Magazine,** compiles a list of vehicles that can be towed four-down behind a motorhome with no modifications required. This guide contains only those vehicles that have been approved by their manufacturers for towing.

Caution: MotorHome® Magazine left out any vehicles that have towing speed limits slower than 55 m.p.h., or distance limits of less than 200 miles. At a minimum, these vehicles require significant modification, such as the use of an aftermarket product, to make them towable. The availability of a **Demco Tow Bar Base Plate** does not imply that these vehicles can be modified or that there is an aftermarket product available. Refer to your vehicle owner's manual or consult your dealer to determine whether your vehicle can be modified to make it towable. Failure to observe this precaution could result in property damage or personal injury.

IMPORTANT INSTALLATION ITEMS

DEMCO products and accessories are intended to be installed by professional installers with experience, proper equipment and the ability to do modification work. Installers with these qualifications can be found in RV and Automotive Service Centers.

If the car to be towed has been in an accident, the chassis may be damaged in an area where the Base Plate attaches. It may no longer be suitable for towing. Extreme caution and careful examination are required in such a situation. It is also likely, even from a minor accident, that the hole alignment will be more difficult due to hole alignment problems.

DEMCO

4010 320th St., Boyden, IA. 51234

Phone: (712) 725-2311

Fax: (712) 725-2380

Toll Free: 1-800-54DEMCO (1-800-543-3626)

Demco warranty policies, operator manuals, and product registration can be found online:

www.demco-products.com