


**NOTE:** MINIMUM BREAK STRENGTH 1000LBS.

REV.	ECN #	DATE	DFTM
A	1681	05/12/98	JD
B	2651	09/16/03	MJ
C	4355	11/19/09	GG
D	4485	3/30/2010	BVDP
E	5689	8/26/2014	GB
F	6546	5/30/2019	JK

POLY BAG PARTS (D)



THE DRAWING AND ALL INFORMATION THERE ON ARE THE PROPERTY OF DEMCO

THIRD ANGLE PROJECTION  
UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES

WEIGHT 0.44  
VOLUME 1.55

DRAWN BY GG  
APPROV. BY JCN  
SAVED BY JK

DATE 11/19/09  
DATE 08/26/14  
DATE 05/30/19

TOLERANCES  
.X = ±.060  
.XX = ±.030  
.XXX = ±.010  
MIN. MACHINE SURFACE 250  
BREAK ALL SHARP EDGES  
BEND AND DRAFT < ±1°

ITEM	PART #	DESCRIPTION	QTY
1	00068	HBOLT 0.2500-20x0.75x0.75-N	1
2	02772	NUT, .25NC LOCK NYLON INSERT	1
3	13730	SAFETY CABLE F/ ACTUATORS	1

DESCRIPTION SAFETY CABLE F/ ACTUATORS		REV F
DRAWING. NO. <b>05408</b>		
SCALE: 1:2	SHEET 1 OF 1	