

## 500 HOUR SALT SPRAY ZINC PLATED

 $\bigcirc$ 

RE	٧.	ECN#	DESCRIPTION	DATE	DFTM	
	Α	3249	CHANGE TO 500 HOUR SALT SPRAY	12/15/2006	JK	](
	В	4358	CHANGED OVERALL LENGTH FROM 4.13 TO 4.00 CHANGED TREAD DEPTH FROM 1.25 TO 1.50 CHANGED HOLE LOCATION FROM .25 TO .188 ADDED .0625 CHAMFER	11/18/2009	BVDP	
(	С	5728	CHANGE PRINT TOLLERANCE TO MATCH GROOVE PIN RANGE TOLLERANCE	10/6/2014	GB	

4010 320TH ST. PO BOX 189 BOYDEN, IOWA 51234 THE DRAWING AND ALL INFORMATION THERE ON ARE THE PROPERTY OF DEMCO VOLUME

THIRD ANGLE PROJECTION UNLESS OTHERWISE SPECIFIEDALL DIMENSIONS ARE IN INCHES WEIGHT

DRAWN BY DATE 01/10/05 billvp DATE 10/06/14 APPOV. BY TL SAVED BY 10/06/14 JCN TOLERANCES

MATERIAL:

MIN. MACHINE SURFACE 250 BREAK ALL SHARP EDGES BEND AND DRAFT ∠ ±1°  $.X = \pm .060$   $.XX = \pm .030$   $.XXX = \pm .010$ 0.39

SROCR2014: STEEL, ROUND, CR 1144, .375 DESCRIPTION CLAMP BOLT DRAWING. NO. REV SCALE: 1:1 SHEET 1 OF 1