


Ⓓ WIRE Ø - 0.063"  
O.D. - .650"  
FREE LENGTH - 3.50"  
SOLID COMPRESSION LENGTH - .750"  
SPRING RATE - 12 LBS./IN.

Ⓑ 500 HOUR SALT SPRAY ZINC PLATED

ⒸⒺ

REV.	DESCRIPTION	DATE	APPROVED	MATERIAL: ASTM 1064 Ø.063 WIRE						
A	CHANGED TOLERANCE FROM ±.03 TO ±.06	8/29/2005	JK	<div>THE DRAWING AND ALL INFORMATION THERE ON ARE THE PROPERTY OF</div> <div>DEMCO</div> <div>4010 320TH STREET BOYDEN, IOWA 51234</div> <div>TOLERANCES</div> <div>.X = ±.060 .XXX = ±.010 NON-MACHINED .XX = ±.030 .XXX = ±.005 MACHINED</div> <div>MIN. MACHINE SURFACE 250 BREAK ALL SHARP EDGES BEND AND DRAFT ≤ 1°</div>	UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES	DRAWN BY billvp	DATE 01/10/05	DESCRIPTION EZ LATCH LEVER SPRING		
B	3249 500 SALT SPRAY	12/15/2006	JK		APPROV. BY JCN	DATE 03/17/21	DRAWING. NO.		REV	
C	CHANGED WIRE SIZE TO .063	6/25/2007	CJ		THIRD ANGLE PROJECTION	WEIGHT 0.02		12020		E
D	ADDED I.D. 3663	1/18/2008	GG		VOLUME 0.08					
E	ADD ASTM 1064 CALL OUT	3/17/2021	JCN		SCALE 1:1					