


NOTES:

- 1.) ALL DIMENSIONS ARE IN INCH UOS
- 2.) .25 DIA. GALVANIZED AIRCRAFT CABLE
- 3.) STRETCH LENGTH OF CABLE IS 24" WITHOUT HOOK
- 4.) ADD THIMBLES ON LOOP ENDS
- 5.) ADD HOOK WITH CLIP TO ONE END, HOOK MUST MOVE FREELY ON CABLE
- 6.) CABLE IN CLEAR COATING/JACKET
- 7.) STRIP COATING FOR ENTIRE LOOP & SLEEVES, 9" EACH END
- 8.) MIN. BREAKING STRENGTH OF ASSEMBLY 7,000 LBS
- 9.) PACKAGING: TIE LOOPS TOGETHER WITH TWIST TIES

REV.	DESCRIPTION	DATE	APPROVED
A	ADDED DIM. TO THIMBLE & NOTE TO HOOK	9/26/2008	JK
B	ADDED NOTE FOR VINYL COATING SWEDGES	3/20/2013	RJW
C	ADDED GALVANIZED TO NOTE	3/18/2019	JCN

THE DRAWING AND ALL INFORMATION THERE ON ARE THE PROPERTY OF DEMCO 4010 320TH STREET BOYDEN, IOWA 51234		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES	DRAWN BY JK DATE 12/05/05	DESCRIPTION CABLE, SAFETY 24" CLEAR JACKET	
THIRD ANGLE PROJECTION			APPROV. BY JCN DATE 03/18/19	DRAWING. NO.	REV
TOLERANCES .X = ±.060 .XXX = ±.010 NON-MACHINED .XX = ±.030 .XXX = ±.005 MACHINED			WEIGHT 1.14	12236	
MIN. MACHINE SURFACE 250 BREAK ALL SHARP EDGES BEND AND DRAFT < ±1°			VOLUME 4.06		
			SCALE 1:2 SHEET 1 OF 1		