



**NOTE:** MINIMUM BREAK STRENGTH 1000LBS.

REV.	ECN #	DATE	DFTM
A	1681	05/12/98	JD
B	2651	09/16/03	MJ
C	4355	11/19/09	GG
D	4485	3/30/2010	BVDP
E	5689	8/26/2014	GB
F	6546	5/30/2019	JK

*Demco*  
4010 320TH ST. PO BOX 189  
BOYDEN, IOWA 51234

THE DRAWING AND ALL  
INFORMATION THERE  
ON ARE THE PROPERTY OF  
DEMCO

THIRD ANGLE  
PROJECTION

UNLESS OTHERWISE  
SPECIFIED ALL DIMENSIONS  
ARE IN INCHES

WEIGHT	0.44
VOLUME	1.55

DRAWN BY	BVDP	DATE	03/30/10
APPROV. BY	TL	DATE	08/26/14
SAVED BY	JK	DATE	05/30/19

TOLERANCES

.X = ±.060	MIN. MACHINE SURFACE 250
.XX = ±.030	BREAK ALL SHARP EDGES
.XXX = ±.010	BEND AND DRAFT $\angle \pm 1^\circ$

DESCRIPTION  
SAFETY CABLE F/ ACTUATORS

DRAWING. NO.

① **13730**

SCALE: 1:2

SHEET 1 OF 1

REV  
**F**