



NOTE DECAL SEAM LOCATION

NOTE: MUST USE GLUE TO ADHERE
 14216 TO 14214
 14214 ZINC PLATED 120 HOUR SALT SPRAY TEST
 14216 SHORE D 35-45 HARDNESS
 UV STABILIZED

ITEM	PART #	DESCRIPTION	QTY
1	14214-95	HITCH HANDLE	1
2	14216	YELLOW GRIP F/ 1.125 RND TUBE	1

Demco
 4010 320TH ST. PO BOX 189
 BOYDEN, IOWA 51234

THIRD ANGLE
 PROJECTION

UNLESS OTHERWISE
 SPECIFIED ALL DIMENSIONS
 ARE IN INCHES

WEIGHT 1.07
 VOLUME 4.48

DRAWN BY JCN

DATE 05/01/17

APPOV. BY TL

DATE 05/01/17

SAVED BY RE

DATE 05/09/19

TOLERANCES

.X = ±.060
 .XX = ±.030
 .XXX = ±.010
 MIN. MACHINE SURFACE 250
 BREAK ALL SHARP EDGES
 BEND AND DRAFT $\angle \pm 1^\circ$

DESCRIPTION
 HJ HANDLE ASSEMBLY

DRAWING. NO.

15934

REV
A

SCALE: 1:2

SHEET 1 OF 1

REV.	ECN #	DESCRIPTION	DATE	DFTM
A	6540	MOVED DECAL LOCATION	5/9/2019	JK

THE DRAWING AND ALL
 INFORMATION THERE
 ON ARE THE PROPERTY OF
 DEMCO