NOTE: MUST USE GLUE TO ADHERE 14216 TO 17050 17050 ZINC PLATED 120 HOUR SALT SPRAY TEST 14216 SHORE D 35-45 HARDNESS UV STABILIZED	ITEM PART # DESCRIPTION QTY   1 14216 YELLOW GRIP F/ 1.125 RND TUBE 1   2 17050 HITCH HANDLE 1   1 14216 YELLOW GRIP F/ 1.125 RND TUBE 1   2 17050 HITCH HANDLE 1   1 14216 YELLOW GRIP F/ 1.125 RND TUBE 1   2 17050 HITCH HANDLE 1   1 12/14/20 DESCRIPTION LATCH HANDLE W/GRIP   4010 320H STREET BOYDEN, IOWA 5124 THIRD ANGLE OF TOLERANCES DESCRIPTION LATCH HANDLE W/GRIP   X = ±.060 XXX = ±.010 NON-MACHINED NO. NO. REV   VOLUME 0.555 SCALE SHEET IIII OLERANCES SCALE SHEET BOYDEN BURD AND DRAFT  YIE   MIN. MACHINE SURFACE 250 SCALE SCALE SHEET IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII