



NOTES:

- 1.) ALL DIMENSIONS ARE IN INCH UOS
- 2.) .25 DIA. CABLE
- 3.) STRETCH LENGTH OF CABLE IS 42" WITHOUT HOOK
- 4.) ADD THIMBLES ON LOOP ENDS
- 5.) ADD HOOK WITH CLIP TO ONE END, HOOK MUST MOVE FREELY ON CABLE
- 6.) CABLE IN CLEAR COATING/JACKET
- 7.) STRIP COATING FOR ENTIRE LOOP & SLEEVES, 9" EACH END
- 8.) MIN. BREAKING STRENGTH OF ASSEMBLY 7200 LBS
- 9.) PACKAGING: TIE LOOPS TOGETHER WITH TWIST TIES

DEMCO <small>4010 320TH STREET BOYDEN, IOWA 51234</small>		<small>THE DRAWING AND ALL INFORMATION THERE ON ARE THE PROPERTY OF DEMCO</small>		<small>DESCRIPTION</small> 7K 42" SAFETY CABLE CLEAR	
<small>THIRD ANGLE PROJECTION</small> 	<small>UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES</small>	<small>DRAWN BY</small> JCN	<small>DATE</small> 09/14/22	<small>DRAWING. NO.</small> 17639	<small>REV</small> 1
<small>TOLERANCES</small> .X = ±.060 .XX = ±.030 .XXX = ±.010	<small>MIN. MACHINE SURFACE 250 BREAK ALL SHARP EDGES BEND AND DRAFT < ±1°</small>	<small>APPROV. BY</small> JCN	<small>DATE</small> 11/15/22	<small>WEIGHT</small> 1.2	<small>VOLUME</small> 1 OF 1