



NOTES:

- 1.) ALL DIMENSIONS ARE IN INCH UOS
- 2.) .313 DIA. CABLE
- 3.) STRETCH LENGTH OF CABLE IS 42" WITHOUT HOOK
- 4.) ADD THIMBLES ON LOOP ENDS
- 5.) ADD HOOK WITH CLIP TO ONE END, HOOK MUST MOVE FREELY ON CABLE
- 6.) CABLE IN BLACK COATING/JACKET
- 7.) STRIP COATING FOR ENTIRE LOOP & SLEEVES, 9" EACH END
- 8.) MIN. BREAKING STRENGTH OF ASSEMBLY 9800 LBS
- 9.) PACKAGING: TIE LOOPS TOGETHER WITH TWIST TIES

| | | | | | | |
|--|--|---|--------------------------------------|---|--|-----------------------------|
| <div>DEMCO</div> <div>4010 320TH STREET BOYDEN, IOWA 51234</div> | | <div>THE DRAWING AND ALL INFORMATION THERE ON ARE THE PROPERTY OF DEMCO</div> | | <div>DESCRIPTION</div> <div>9.8K 42" SAFETY CABLE BLACK</div> | | |
| <div>THIRD ANGLE PROJECTION</div> <div></div> | <div>UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES</div> | | <div>DRAWN BY</div> <div>BM</div> | <div>DATE</div> <div>09/15/22</div> | <div>DRAWING. NO.</div> <div>17643</div> | <div>REV</div> <div> </div> |
| | | | <div>APPROV. BY</div> <div>JCN</div> | <div>DATE</div> <div>11/15/22</div> | | |
| <div>TOLERANCES</div> <div>.X = ±.060 MIN. MACHINE SURFACE 250</div> <div>.XX = ±.030 BREAK ALL SHARP EDGES</div> <div>.XXX = ±.010 BEND AND DRAFT ≤ ±1°</div> | | | <div>WEIGHT</div> | <div>VOLUME</div> | <div></div> | |
| | | | <div>SCALE</div> <div>1:2</div> | <div>SHEET</div> <div>1 OF 1</div> | | |