



NOTES:

- 1.) ALL DIMENSIONS ARE IN INCH UOS
- 2.) .313 DIA. CABLE
- 3.) STRETCH LENGTH OF CABLE IS 60" WITHOUT HOOK
- 4.) ADD THIMBLES ON LOOP ENDS
- 5.) ADD HOOK WITH CLIP TO ONE END, HOOK MUST MOVE FREELY ON CABLE
- 6.) CABLE IN BLACK COATING/JACKET
- 7.) STRIP COATING FOR ENTIRE LOOP & SLEEVES, 9" EACH END
- 8.) MIN. BREAKING STRENGTH OF ASSEMBLY 9800 LBS
- 9.) PACKAGING: TIE LOOPS TOGETHER WITH TWIST TIES

<div>DEMCO</div> <div>4010 320TH STREET BOYDEN, IOWA 51234</div>		THE DRAWING AND ALL INFORMATION THERE ON ARE THE PROPERTY OF DEMCO		DESCRIPTION 9.8K 60" SAFETY CABLE BLACK		
THIRD ANGLE PROJECTION		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES	DRAWN BY BM	DATE 09/15/22	DRAWING. NO. <div>17646</div>	REV _
			APPROV. BY JCN	DATE 11/15/22		
TOLERANCES .X = ±.060 .XX = ±.030 .XXX = ±.010 MIN. MACHINE SURFACE 250 BREAK ALL SHARP EDGES BEND AND DRAFT ≤ ±1°			WEIGHT	VOLUME		
			SCALE 1:2	SHEET 1 OF 1		