



NOTES:

- 1.) ALL DIMENSIONS ARE IN INCH UOS
- 2.) .375 DIA. CABLE
- 3.) STRETCH LENGTH OF CABLE IS 42" WITHOUT HOOK
- 4.) ADD THIMBLES ON LOOP ENDS
- 5.) ADD HOOK WITH CLIP TO ONE END, HOOK MUST MOVE FREELY ON CABLE
- 6.) CABLE IN BLUE COATING/JACKET
- 7.) STRIP COATING FOR ENTIRE LOOP & SLEEVES, 9" EACH END
- 8.) MIN. BREAKING STRENGTH OF ASSEMBLY 14000 LBS
- 9.) PACKAGING: TIE LOOPS TOGETHER WITH TWIST TIES

DEMCO 4010 320TH STREET BOYDEN, IOWA 51234		THE DRAWING AND ALL INFORMATION THERE ON ARE THE PROPERTY OF DEMCO		DESCRIPTION 14K 42" SAFETY CABLE BLUE	
THIRD ANGLE PROJECTION		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES	DRAWN BY BM	DATE 09/15/22	DRAWING. NO. 17647
		TOLERANCES MIN. MACHINE SURFACE 250 BREAK ALL SHARP EDGES BEND AND DRAFT $\angle \pm 1^\circ$	APPROV. BY JCN	DATE 11/15/22	REV 1
.X = $\pm .060$.XX = $\pm .030$.XXX = $\pm .010$			WEIGHT 1.2	VOLUME 1 OF 1	