


# NOTES:

- 1.) ALL DIMENSIONS ARE IN INCH UOS
- 2.) .375 DIA. CABLE
- 3.) STRETCH LENGTH OF CABLE IS 60" WITHOUT HOOK
- 4.) ADD THIMBLES ON LOOP ENDS
- 5.) ADD HOOK WITH CLIP TO ONE END, HOOK MUST MOVE FREELY ON CABLE
- 6.) CABLE IN BLUE COATING/JACKET
- 7.) STRIP COATING FOR ENTIRE LOOP & SLEEVES, 9" EACH END
- 8.) MIN. BREAKING STRENGTH OF ASSEMBLY 14000 LBS
- 9.) PACKAGING: TIE LOOPS TOGETHER WITH TWIST TIES

<div>DEMCO</div> <div>4010 320TH STREET BOYDEN, IOWA 51234</div>		<div>THE DRAWING AND ALL INFORMATION THERE ON ARE THE PROPERTY OF DEMCO</div> <div>UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES</div>		<div>DESCRIPTION</div> <div>14K 60" SAFETY CABLE BLUE</div>	
<div>THIRD ANGLE PROJECTION</div> <div></div>		<div>DRAWN BY</div> <div>BM</div> <div>DATE</div> <div>09/19/22</div>		<div>DRAWING. NO.</div> <div>17650</div> <div>REV</div> <div></div>	
<div>TOLERANCES</div> <div>.X = ±.060</div> <div>.XX = ±.030</div> <div>.XXX = ±.010</div>		<div>MIN. MACHINE SURFACE 250</div> <div>BREAK ALL SHARP EDGES</div> <div>BEND AND DRAFT ≤ ±1°</div>		<div>WEIGHT</div> <div>VOLUME</div> <div>SCALE</div> <div>1:2</div> <div>SHEET</div> <div>1 OF 1</div>	
<div></div>					